



4-Seat (2+2) A-series Electric Quick Shuttle



| | | | | |
|--------------------|--|-------|--------------|--------------|
| Model No. | A2+2-36 (values are approximate) | | | |
| Power | | | | |
| Motor | 36V DC, 3.0 kW | | | |
| Battery | Not Included | | | |
| Charger | Onboard Charger | | | |
| Transaxle | Continuously variable, 10.25:1 high speed rear axle | | | |
| Controller | 275 amp | | | |
| Structure | | | | |
| Chassis | A-Frame Powder coated steel; 4-wheel coil springs over shocks | | | |
| Top supports | Galvanized steel - anti-corrosive dipped and powder coat paint | | | |
| Body | PP Material | | | |
| Overall dimension | 9 x 4 x 6 ft | | | |
| Ground clearance | 4.5 in | | | |
| Net weight | 639 lbs | | | |
| Equipment | | | | |
| Lights | Head | Tail | Brake | Turn signals |
| Other | State of charge | Horn | Speedometer | Side mirrors |
| | Rear seat kit installed | | 2+2 long top | |
| Wheels | 10" aluminum | | | |
| Performance | | | | |
| Loading | 4 people | | | |
| Forward speed | Standard DC drive: 14-19 mph; | | | |
| Braking distance | 7 ft | | | |
| Turning radius | 10 ft | | | |
| Climbing ability | safe climbing:25%/Max climbing:35% | | | |
| Maximum mileage | Standard DC drive: 50-62 miles; | | | |
| Options | | | | |
| Windshield | Rain Enclosure | Color | | |